

# Session 2

# Footings & Foundations

## (Concrete & Formwork)



QS TRAINING.IN

*2021 Tradida QS Global Solutions LLP*

*All rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopy, recording or any information storage or retrieval system, without permission in writing from the publisher*

**TRADIDA QS**  
Global Solutions LLP


# Types of Footings & Foundation

- Isolated Footing
- Strip Footing
- Raft Foundation
- Pile Foundation


# ISOLATED FOOTINGS



# Types of Isolated Footings



# Isolated footings – Formwork arrangement




Formwork arrangement

## Perimeter -

- $(Length + Breadth) \times 2$
- $(Length + Length + Breadth + Breadth)$

[www.qstraining.in](http://www.qstraining.in)

# Isolated footings – Quantification




**TYPICAL SECTION  
(STRUCTURAL DRG)**

Concrete – Volume – m3  
Length X Breadth X Depth

Formwork – Area – m2  
Perimeter of footing x depth

# Isolated footings – Quantification



[www.qstraining.in](http://www.qstraining.in)


## FOOTING SCHEDULE

FOOTING MKD.	FOOTING SIZE		
	A	B	Z
F1	2000	2000	500
F2	2000	2000	550
F3	1600	1600	450
F4	1800	1800	400
F5	2100	1800	400

Description	Nos	L	B	D	Quantity	Unit
Concrete – F5	4	2.1	1.8	0.40	6.048	M <sub>3</sub>
Form Work – F5	4	$(2.1 + 1.8) * 2$		0.40	12.48	M <sub>2</sub>



# Isolated footings – Quantification



## FOOTING SCHEDULE

Type	A	B	Z	Nos
F1	1500	1750	350	3
F2	1500	2200	400	1
F3	1400	2000	400	1
F4	1500	1500	300	2

[www.qstraining.in](http://www.qstraining.in)

**STRUCTURAL DRAWING**  
**FOUNDATION PLAN**




# Isolated footings – Quantification


[www.qstraining.in](http://www.qstraining.in)

Description	Ref	Nos	L	B	D	Quantity	Unit
<b>Concrete</b>							
F1		3	1.50	1.75	0.35	2.76	
F2		1	1.50	2.2	0.4	1.32	
F3		1	1.40	2.0	0.4	1.12	
F4		2	1.50	1.5	0.3	1.35	
						<b>6.55</b>	<b>M3</b>
<b>Formwork</b>							
F1		3	6.50		0.35	6.825	
F2		1	7.40		0.4	2.960	
F3		1	6.80		0.4	2.720	
F4		2	6.00		0.3	3.600	
						<b>16.105</b>	<b>M2</b>

# PCC / Blinding Concrete



TYPICAL FOOTING SECTION




Concrete - Volume - m<sup>3</sup>  
Formwork - Area - m<sup>2</sup>

Note - In GCC some clients doesn't pay formwork required for blinding concrete separately, In such cases formwork expenses should be added as part of blinding concrete cost.


## PRICING PREAMBLES

The rates for plain (unreinforced) concrete below formation level are to include for all necessary formwork to sides, edges and top surfaces to a slop exceeding 15 degrees from horizontal where required

# PCC / Blinding Concrete





TYPICAL FOOTING SECTION




Concrete - Volume - m<sup>3</sup>  
Formwork - Area - m<sup>2</sup>

Description	Ref	Nos	L	B	D	Quantity	Unit
Concrete – F5		4	2.3	2.0	0.10	1.84	M <sub>3</sub>
Form work – F5		4	$(2.3 + 2.0) * 2$ = 8.6	-	0.10	3.44	M <sub>2</sub>

# Sloped Footing




# Sloped Footing



TYPICAL FOOTING SECTION




PLAN AT BOTTOM



PLAN AT TOP

# Sloped Footing



Volume of Part A  
$$\frac{h}{3} \times [A1 + A2 + \text{Sqrt}(A1 \times A2)]$$

H – Height of trapezoidal portion  
A1 – Area at Bottom of trapezoidal portion  
A2 – Area at Top of trapezoidal portion

## Volume of part B

$$1.7\text{m} \times 2.5\text{m} \times 0.2\text{m} = \underline{0.85 \text{ m}^3}$$

## Volume of part A


$$A1 = 1.7 \times 2.5 = 4.25\text{m}^2 \text{ and } A2 = 0.45 \times 0.6 = 0.27\text{m}^2$$
$$0.55/3 \times [4.25 + 0.27 + \text{sqrt}(4.25 \times 0.27)] = \underline{1.03 \text{ m}^3}$$

## VOLUME OF FOOTING


$$0.85\text{m}^3 + 1.03\text{m}^3 = \underline{1.88 \text{ m}^3}$$

# Sloped Footing

[www.qstraining.in](http://www.qstraining.in)



PLAN



SECTION

SI No.	Description	Nos.	L	B	D	Unit	Quantity
<b>1</b>	<b>Concrete</b>						
1.1	Flat portion	1	1.6	1.6	0.2	M <sub>3</sub>	0.512
1.2	Slope Portion	1	$A_1 + A_2 + \text{SQRT} ( A_1 * A_2 )$ $(1.6 \times 1.6) + (0.8 \times 0.8) +$ $\text{SQRT}((1.6 \times 1.6) * (0.8 \times 0.8))$		0.3/3	M <sub>3</sub>	0.448
<b>2</b>	<b>Formwork</b>						
2.1	Side formwork for flat portion	1	$2 \times (1.6 + 1.6)$		0.2	M <sub>2</sub>	1.28



# RAFT FOUNDATION




# Raft Foundation

[www.qstraining.in](http://www.qstraining.in)


## Applications

Building Basement floor  
Water Tank floor




Concrete =	Length	X Breadth	X Depth	Volume of concrete	M <sup>3</sup>
Shuttering / formwork =	(Length + Breadth) x 2	-	X Depth	Area of formwork	M <sup>2</sup>

# Raft Foundation



**STRUCTURAL LAYOUT**



**SECTION**

**C - COLUMN**


**TB - TIE BEAM**  
**RB - RAFT BEAM**

Description	Ref	Nos.	L	B	D	Quantity	Unit
Concrete		1	13.3	13.3	0.43	76.06	M <sub>3</sub>
Formwork		1	(13.3+13.3) × 2		0.43	22.88	M <sub>2</sub>





# Raft Foundation – Lift Core



[www.qstraining.in](http://www.qstraining.in)

Description	Ref	Nos.	L	B	D	Quantity	Unit
Concrete		1	3.8	3.8	0.8	11.55	M <sub>3</sub>
Formwork		1	$(3.8 + 3.8) \times 2$		0.8	12.16	M <sub>2</sub>


# STRIP FOOTING





# Strip Footing

[www.qstraining.in](http://www.qstraining.in)




Concrete =	No.	Length	x Breadth	x Depth	Volume of concrete	M <sub>3</sub>
Shuttering / formwork =	No. x 2 sides	Length	-	x Depth	Area of formwork	M <sub>2</sub>




# Strip Footing – Boundary Wall

[www.qstraining.in](http://www.qstraining.in)





**STRUCTURAL / ARCHITECTURAL PLAN**




Description	Ref	Nos.	L	B	D	Quantity	Unit
RC Concrete		1	8 x 3	1.5	0.3	10.80	M <sub>3</sub>
Formwork		1 x 2	8 x 3	-	0.3	14.40	M <sub>2</sub>
PC Concrete		1	8 x 3	1.5 + 0.1	0.1	3.84	M <sub>3</sub>
Formwork		1 x 2	8 x 3		0.1	4.80	M <sub>2</sub>

# Strip Footing – Boundary Wall




Description	Ref	No	L	B	D	Quantity	Unit
PCC Concrete		1	24	1.2	0.1	2.88	M <sub>3</sub>
PCC Formwork		2	24		0.1	4.8	M <sub>2</sub>
<b>Concrete</b>							
Footing - Step 1		1	24	1	0.25	6.0	M <sub>3</sub>
Footing - Step 2		1	24	0.4	0.3	2.88	M <sub>3</sub>
<b>Formwork</b>							
Footing - Step 1		2	24		0.25	12.0	M <sub>2</sub>
Footing - Step 2		2	24		0.30	14.4	M <sub>2</sub>

# Strip Footing – Boundary Wall



**PLAN AT GROUND LVL**


[www.qstraining.in](http://www.qstraining.in)



**SECTION**

Description	Ref	Nos.	L	B	D	Qty	Unit
Concrete		1	30.25	2.65	0.45	36.07	M <sup>3</sup>
Formwork		2 Sides	30.25		0.45	27.23	M <sup>2</sup>

# Strip Footing – All Round Building




## Centreline Method

**Thickness of Strip footing  
250mm**

[www.qstraining.in](http://www.qstraining.in)

Description	Nos.	L	B	D	Qty	Unit
Concrete	1	$((\frac{1}{2} + 4.5 + \frac{1}{2}) + (\frac{1}{2} + 3.5 + \frac{1}{2})) \times 2 = 20$	1.00	0.25	5.00	M <sub>3</sub>
Formwork	2 Sides	20		0.25	10.00	M <sub>2</sub>

# Strip Footing – All Round Building



## Longwall / Short wall Method

**Thickness of Strip footing  
250mm**


[www.qstraining.in](http://www.qstraining.in)

Description	Ref	Nos.	L	B	D	Qty	Unit
Concrete – Long wall	Out to Out	2	1+4.5+ 1	1.00	0.25	3.25	M <sub>3</sub>
Concrete – Short Wall	In to In	2	3.5	1.00	0.25	1.75	M <sub>3</sub>
Formwork		2 X 2	6.5		0.25	6.5	M <sub>2</sub>
Formwork		2 X 2	3.5		0.25	3.5	M <sub>2</sub>

# PILE FOUNDATION



# Pile Foundation



Pile Boring



Pile Concreting



Piling work  
completed site



Breaking of Pile  
Head




# Pile Foundation

## Applications

Weak Soil conditions  
Buildings / Bridges / Fly overs


$$Volume - Depth \times \pi r^2$$



Concrete	Nos.	Pile radius <sup>2</sup>	$\pi$	x Depth of pile	Volume of concrete	m <sup>3</sup>
Boring Length	Nos.	-	-	x Depth of pile	Total boring length	m
Breaking pile head	Nos.	Pile radius <sup>2</sup>	$\pi$	x 1 m or as indicated in drawing	Volume of demolition	m <sup>3</sup>

# Pile Foundation

**PL – PILE LENGTH**  
**SL – SOCKETING LENGTH**




BORED PILE DIAMETER (mm)	MAIN REINFTS	SPIRAL LINKS	REINFTS LENGTH	TOTAL No. OF PILE	PILE COMPRESSION CAPACITY (kN)	ESTIMATED PENETRATION PL = PILE LENGTH FR	
						ZONE 1	
						BH1, BH2, BH3 BH2A, BH4, BH5	
						PL (M)	SL (M)
600	9T16	T10-175	VARIES	REFER TO LAYOUT DRG.	1600	13	5

[www.qstraining.in](http://www.qstraining.in)

Description	Ref	Nos.	L	B	D	Quantity	Unit
Concrete	Pile – P1	1	$0.30^2$	$\pi$	13	3.68	M <sup>3</sup>
Boring of Pile	Pile – P1	1	-	-	13	13.00	M
Breaking of Pile Head	Pile – P1	1	$0.30^2$	$\pi$	1	0.28	M <sup>3</sup>

# Pile Foundation



**PILE FOUNDATION LAYOUT PLAN**

**P1** - 600Ø Pile (12m. Depth)

**P2** - 700Ø Pile (12m. Depth)

Note – breaking of pile head, depth may vary according to different projects.

Description	Ref	Nos.	L	B	D	Quantity	Unit
Concrete	Pile – P2	4	$0.35^2$	$\pi$	12	18.47	M <sup>3</sup>
Boring of Pile	Pile – P2	4	-	-	12	48.00	M
Breaking of Pile Head	Pile – P2	4	$0.35^2$	$\pi$	1	1.54	M <sup>3</sup>



# *Thanks!*

Any questions?

You can find me at:

- [tradidaqs@outlook.com](mailto:tradidaqs@outlook.com)
  - +91 9539 141 777
- 